

AXIS Q1942-E Thermal Network Camera

Outstanding VGA detection and powerful video analytics

AXIS Q1942-E is an affordable outdoor, bullet style, thermal camera with a built-in window heater for harsh weather conditions. A resolution of 640x480 and a range of lens alternatives (10 mm, 19 mm, 35 mm and 60 mm) make it possible to optimize detection performance to meet most requirements. It supports Electronic Image Stabilization that keeps the video smooth during vibrations, and Axis Zipstream that lowers bandwidth and storage requirements. Thanks to its powerful processor, AXIS Q1942-E has high capacity for running video analytics via AXIS Camera Application Platform (ACAP) and can use a range of third party applications.

- > [VGA resolution](#)
- > [High performance for video analytics](#)
- > [Reliable detection and fast verification](#)
- > [Electronic Image Stabilization](#)
- > [Axis Zipstream technology](#)



AXIS Q1942-E Thermal Network Camera

Models	AXIS Q1942-E 10 mm/19 mm/35 mm or 60 mm	Overlay text, play audio clip
Camera		Data streaming Event data
Image sensor	Uncooled Micro bolometer 640x480, pixel size: 17 µm Spectral range: 8-14 µm	Built-in installation aids Pixel counter
Lens	Athermalized 10 mm Horizontal field of view: 63°, F1.24 Near focus distance: 2.8 m (9.2 ft) 19 mm Horizontal field of view: 31°, F1.23 Near focus distance: 9.2 m (30 ft) 35 mm Horizontal field of view: 17°, F1.20 Near focus distance: 33 m (108 ft) 60 mm Horizontal field of view: 10°, F1.25 Near focus distance: 91 m (300 ft)	General
Sensitivity	NETD < 50 mK	Casing IP66-, IP67- and NEMA 4X-rated Metal casing (aluminum) with integrated dehumidifying membrane and a germanium window Color: White NCS S 1002-B
Video		Sustainability PVC free
Video compression	H.264 (MPEG-4 Part 10/AVC) Baseline, Main and High Profiles Motion JPEG	Memory 512 MB RAM, 256 MB Flash
Resolution	Sensor is 640x480. Image can be scaled up to 800x600 (SVGA).	Power Power over Ethernet IEEE 802.3af/802.3at Type 1 Class 3 Typical 4.8 W, max 11.8 W 8-28 V DC, typical 6.6 W, max 13 W 20-24 V AC (50/60 Hz), typical 11 VA, max 19 VA Power supply not included.
Frame rate	Up to 8.3 fps and 30 fps	Connectors RJ45 10BASE-T/100BASE-TX PoE I/O connector for DC or AC input, two configurable inputs/outputs and mic in/line in, line out, (AXIS Multicable A I/O Audio not included), AC/DC input
Video streaming	At least three H.264 and Motion JPEG streams, simultaneous and individually configured in max. resolution in full frame rate Axis Zipstream technology in H.264 Controllable frame rate and bandwidth VBR/ABR/MBR H.264	Storage Support for microSD/microSDHC/microSDXC card Support for SD card encryption Support for recording to network-attached storage (NAS) For SD card and NAS recommendations see axis.com
Image settings	Compression, brightness, sharpness, contrast, exposure zone, text and image overlay, privacy mask, mirroring of images, electronic image stabilization, multiple palettes Rotation: 0°, 90°, 180°, 270° including Corridor Format	Operating conditions -40 °C to 60 °C (-40 °F to 140 °F) Humidity 10-100% RH (condensing) De-icing capability, compliant to MIL-STD-810F Method 521.3
Audio		Storage conditions -40 °C to 70 °C (-40 °F to 158 °F)
Audio streaming	Two-way, full duplex	Approvals EMC EN 55022 Class A, EN 50121-4, IEC 62236-4, EN 55024, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class A, ICES-003 Class A, VCCI Class A, RCM AS/NZS CISPR22 Class A, KCC KN32 Class A, KN35
Audio compression	24bit LPCM, AAC-LC 8/16 kHz, G.711 PCM 8 kHz, G.726 ADPCM 8 kHz, Opus 8/16/48 kHz Configurable bit rate	Safety IEC/EN/UL 60950-1, IEC/EN/UL 60950-22 IEC/EN/UL 60950-1, IEC/EN/UL 60950-22, IS 13252
Audio input/output	External microphone input or line input, line output	Environment EN 50581, NEMA 250 Type 4X, IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-6 Class 4M4, IEC 60068-2-27, IEC 60068-2-52, IEC 60721-3-4 Class 4K3, MIL-STD-810F Method 521.3 IEC 60529 IP66/IP67
Network		Network NIST SP500-267
Security	Password protection, IP address filtering, HTTPS ^a encryption, IEEE 802.1x (EAP-TLS) ^a network access control, digest authentication, user access log, centralized certificate management, brute force delay protection, signed firmware	Dimensions 344 x 146 mm (13 9/16 x 5 3/4 in)
Supported protocols	IPv4, IPv6 USGv6, HTTP, HTTPS ^a , SSL/TLS ^a , QoS Layer 3 DiffServ, FTP, CIFS/SMB, SMTP, Bonjour, UPnP TM , SNMP v1/v2c/v3 (MIB-II), DNS, DynDNS, NTP, RTSP, RTP, SRTP, SFTP, TCP, UDP, IGMP, RTCP, ICMP, DHCP, ARP, SOCKS, SSH, LLDP	Weight 10/19/35 mm: 2000 g (4.4 lb) 60 mm: 2200 g (4.9 lb)
System integration		Included accessories Resistorx [®] L-key, wall and ceiling mount bracket terminal block connector Installation Guide, Windows [®] decoder 1-user license
Application Programming Interface	Open API for software integration, including VAPIX [®] and AXIS Camera Application Platform; specifications at axis.com AXIS Video Hosting System (AVHS) with One-Click Connection ONVIF [®] Profile G and ONVIF [®] Profile S specification at onvif.org	Optional accessories AXIS T98A17-VE Surveillance Cabinet, AXIS T94G01P, AXIS T91A47 Pole Mount, AXIS Multicable A I/O Audio, Axis PoE Midspans, AXIS T8129 PoE Extender, AXIS T8640 PoE+ over Coax Adapter Kit, AXIS T8604 Media Converter Switch AXIS T8415 Wireless Installation Tool For more accessories, see axis.com
Analytics	Included AXIS Video Motion Detection, AXIS Motion Guard, AXIS Fence Guard, AXIS Loitering Guard, audio detection, active tampering alarm Supported AXIS Perimeter Defender Support for AXIS Camera Application Platform enabling installation of third-party applications, see axis.com/acap	Video management software AXIS Companion, AXIS Camera Station, Video management software from Axis' Application Development Partners available at axis.com/vms
Event triggers	Analytics, temperature, external input, time scheduled, edge storage events	Languages English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese, Traditional Chinese
Event actions	Record video: SD card and network share Upload of images or video clips: FTP, SFTP, HTTP, HTTPS network share and email Pre- and post-alarm video or image buffering for recording or upload Notification: email, HTTP, HTTPS, TCP and SNMP trap	Warranty Axis 3-year warranty and AXIS Extended Warranty option, see axis.com/warranty
		Export control This product is subject to export control regulations. You should always consult and comply with the regulations of the appropriate local export control authorities.

a. This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (www.openssl.org), and cryptographic software written by Eric Young (ey@cryptsoft.com).

Environmental responsibility:

axis.com/environmental-responsibility