

AXIS S1116 Racked

Out-of-the box ready rack server for high-definition surveillance

AXIS Camera Station S1116 Recorder is an out-of-the-box ready rack server validated for reliable high-definition surveil-lance up to 4K. For quick and easy installation, AXIS S1116 is preconfigured and preloaded with AXIS Camera Station video management software including licenses for 16 channels plus all necessary system software. The system configuration can easily be imported from AXIS Site Designer, and AXIS Camera Station lets users take full advantage of Axis wide range of video surveillance devices. With enterprise-grade hard disks, operating system stored on solid-state drive (SSD), and expandable storage capacity, AXIS S1116 provides high-performance and reliability for your system.

- > Ease of installation
- > AXIS Camera Station licenses included
- > Full compatibility with Axis products
- > 3-year hardware warranty with on-site replacement service



www.cxis.com T10132460/EN/M5.3/2003

	AXIS S11
Licenses	16 AXIS Camera Station core licenses included, can be upgraded up to 32 licenses (sold separately)
Processor	Intel® Core i5
Memory	8 GB
Storage	8 TB (1x8 TB) Enterprise Class HDD, 7200 rpm Additional storage: 16 TB (2 free bays)
RAID	RAID levels: 0, 1
Operating system	Microsoft® Windows® 10 IoT Enterprise SAC Built-in operating system recovery: yes Operating system drive: 256 GB SSD
Video streaming	Not intended for local viewing of video. Recommended to use Axis desktop terminals.
Recording	Qualified for recording up to 32 video channels with a total recording rate up to 256 Mbit per second.
Power	550 W (100 - 240 V AC, 50/60 Hz, 7.4 - 3.7 A)
Connectors	2x USB 3.1 1x USB 3.1 Type-C 2x Ethernet (RJ45): 1x 1 GbE / 1x 10 GbE 2x USB 3.1 Type-C / DisplayPort™ 1x Universal audio jack 1x Serial port 1x SD card reader

Operating conditions	10 °C to 35 °C (50 °F to 95 °F) Humidity 10–85% RH (non-condensing)
Storage conditions	-40 °C to 65 °C (-40 °F to 149 °F)
Approvals	EMC EN 55032 Class A, EN 55024, EN 61000-3-2, EN 61000-3-3, FCC Part 15 Subpart B Class A, ICES-3(A)/NMB-3(A), RCM AS/NZS CISPR 32 Class A, VCCI Class A, KC KN 32 Class A KC KN 35 Safety IEC/EN/UL 60950-1, NOM, BSMI, EAC
Dimensions	589 x 482 x 43 mm (23.1 x 19 x 1.67 in)
Weight	9.6 kg (21 lb)
Included accessories	Rack rails, power cord for rack mounting, USB-C to VGA adapte
Optional accessories	Axis desktop terminals For more accessories, see <i>axis.com</i>
Warranty	Axis 3-year warranty and AXIS Extended Warranty option, see axis.com/warranty

Environmental responsibility:

axis.com/environmental-responsibility

